



Certificate number: 2501716 1)

Issued 13/01/2025

Expires 13/01/2030

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Flexipipe-Flexigas Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Flexipipe-Flexigas Ltd
494
37 Westminster Buildings
Theatre Square
Nottingham
NG1 6LG
United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2501716

The following products belong to this certificate

<p>PRODUCT DESCRIPTION Range of RidgeLock™ sets consisting of Ridgeline corrugated stainless steel tubing and sealing rings connected using EN 1254-2 brass fittings to achieve a compression connection.</p>
<p>MODEL(S) R15 15mm Ridgeline Hot / Cold water tube R22 22mm Ridgeline Hot / Cold water tube R28 28mm Ridgeline Hot / Cold water tube A15 15mm Adapter Set A22 22mm Adapter Set A28 28mm Adapter Set</p>
<p>SIZE: See model.</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 5.0 Bar & maximum operating temperature 85°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C. Unless specified in the individual approval, the products within this section are not suitable for below ground use.</p>
<p>MARKING Ridgeline, model and metal grade printed on body.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES N/A.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes